



Havoline® ProDS V SAE 5W-30

Premium Performance mid SAPS synthetic engine lubricant

Product Data Sheet

Customer benefits

- Premium mid SAPS formulation offers reduced exhaust emissions, extended DPF and TWC performance and service life.
- Advanced synthetic designed promotes engine protection over extended drain intervals, offering reduced service and costs.
- Formulated for dependable low temperature fluidity, rapid oil circulation and reliable engine protection during cold start-up
- Efficient keep-clean additive technology helps reduce harmful deposit and sludge formation, offering extended engine life.
- Robust synthetic base oil formulation offers reduced engine oil volatility and helps minimize oil consumption
- Effective keep-clema performance helps promote improved fuel economy and minimized exhaust emissions.

Applications

- Havoline ProDS V SAE 5W-30 is suitable for a large number of Volkswagen/Audi group gasoline and diesel passenger cars or light duty diesel vans- with or without a turbocharger; especially designed for extended drain intervals in Europe and is mandatory for VW/Audi diesels with DPF.
- Havoline ProDS V SAE 5W-30 is recommended for vehicles reuiring VW 504 00/ 507 00 approved engine oil, in practice also called VW Longlife III oils and is backwards compatible with other active and obsolete VW-Audi engine oil specifications.
- Havoline ProDS V SAE 5W-30 may not be suitable for some engines. Always consult owner's manual or handbook if in doubt.

Product description:

- Premium performance synthetic mid SAPS engine lubricant specially formulated with advanced technology additives to meet demanding OEM specifications including Volkswagen-Audi 504 00/507 00 engine lubricant requirements.

A Chevron company product

All trademarks are property owned by Chevron Africa-Pakistan Services (Proprietary) Limited or Chevron Intellectual Property LLC and licensed to Astron Energy Proprietary Limited.





Performance Standards

- Mercedes Benz, MB-Approval 229.51
- BMW, Longlife 04
- VW, VW 504 00/507 00
- Porsche C30

Meets the requirements of

- ACEA C3
- API SN
- Mercedes Benz, MB-229.31

Suitable for use in

- Chrysler MS-11106
- VW 502 00/505 01 engines
- ACEA C2 engines *

** Please note user will not receive fuel economy benefits*



Havoline® ProDS V SAE 5W-30

Premium Performance mid SAPS synthetic engine lubricant

continued

Typical key properties

HAVOLINE ProDS V 5W-30 KEY PROPERTIES	RESULTS
SAE Grade	5W-30
Product Code	500218
Base No., D2896, mg KOH/g	8.7
Phosphorus, m %	0.08
Sulfated Ash, m %	0.8
Viscosity, mm ² /s @ 40°C	66.1
Viscosity, mm ² /s @ 100°C	11.8

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Lubricants; Africa, Middle East and Pakistan.

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltexoils.com.

For more information, go to www.chevronlubricants.com

A Chevron company product

All trademarks are property owned by Chevron Africa-Pakistan Services (Proprietary) Limited or Chevron Intellectual Property LLC and licensed to Astron Energy Proprietary Limited.

HVLNEPRODS V/SA/PDSv2_20/01/2020

© 2020 Chevron Lubricants used under license. All rights reserved.